



COMPANÍA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL MOTOSIERRAS

GLOBAL RACING OIL MOTOSIERRAS SAE 30 is a paraffinic and neutral base lubricant. Its high viscosity confers HIGH ADHESIVENESS adapted for the lubrication of saw chains.

GRO MOTOSIERRAS presents the following properties:

- Good flexibility and adherence.
- High lubrication capacity.
- Low consumption level and low oil losses.
- Good antiwear capacity.

Density at 15 °C	0,89
Viscosity at 40 °C	85 – 110
Viscosity Index	80 min.
Flash point	230 min.
Pour point	- 6 max.
Color	Dark brown

Quality level: DIN 51501.L-AN, ISO 6743/1.L-AN

REV: 10/19

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANÍA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

