



COMPANÍA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL POCLAIN

SPECIAL HYDRAULIC OIL FOR CIVIL WORKS MACHINERY

Description and applications:

Hydraulic oil for oildynamic circuits of high index of viscosity, with antiwear and Extreme Pressure additives. Specially suitable for hydraulic circuits of:

- Public Works Machinery and Earthworks Machinery.
- Automatic transmissions.
- Par Converters.
- Agricultural machinery.
- Wheelbarrows stackers.

Properties:

- It complies with the norm POCLAIN PPM
- High Index of viscosity
- Seals compatible
- Compatible with any type of Steel and Bronzes
- Very good index of desemulsion. Fast water separation.

Specifications:

- POCLAIN PPM (PO 00552-13/P)
- DIN 51524 Parte 2,3, NFE 48600 HVLP
- Denison HF1-HF2

Technical characteristics:

Typical values

Aspect		Clear blue
Density at 15 °C	ASTM D-1298	0,86
Viscosity at 40 °C	ASTM D-445 cSt	48
Viscosity Index	ASTM D-2270	170 min.
Flash point	ASTM D-92 °C	> 190
Pour point	ASTM D-97 °C	- 36 max.
Index desemulsion	ASTM D-1401	15
Vickers v-104 C	250 h.mg.	10 max.

Revision 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANÍA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

