



COMPAÑIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL SPECIAL 10W40

GLOBAL SPECIAL 10W40 is a long life semisynthetic oil lubricant for Diesel and gasoline engines of city cars and commercial vans.

PROPERTIES

- Semisynthetic SAE 10W40 multigrade
- High level of detergency and dispersancy
- Maximum antiwear characteristics.
- Low friction coefficient and easy cold start.
- Very high shear resistance

ADVANTAGES

- High alkalinity reserve
- Very big detergency
- Reduces fuel consumption
- Reduces maintenance costs

TECHNICAL CHARACTERISTICS

	Norme	Typical Values	Units
SAE	-	10W40	-
Viscosity at 40°C	ASTM D-445	110	mm ² /s
Viscosity at 100°C	ASTM D-445	15	mm ² /s
Viscosity Index	ASTM D-2270	150	-
Pour point	ASTM D-97	-30	°C
Flash point	ASTM D-92	220	°C
TBN	ASTM D-2896	8,5	-
Aditives	Antiwear, detergency, dispersants, antioxidants, antirust y antifoaming.		-

It meets standards:

API SL
ACEA- A3/B3/B4
MB 229,1 VW 501.00 / 505.00

Rev : 08/18

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPAÑIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

