



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

BIKER HC 10W40

Synthetic lubricant for 4-stroke motorcycle engines.

DESCRIPTION

Synthetic lubricant for all types of motorcycles... 4-stroke engines, with or without integrated gearboxes and oil-bathed or dry clutch, engines that meet euro 2, 3, 4 and 5 anti-pollution standards equipped with exhaust gas treatment systems such as catalysts, air injection in the exhaust.

Other applications: motorcycles without catalytic converters, scooters, quads, mopeds...

PERFORMANCE

STANDARDS: API SM
JASO MA2

The jaso MA2 standard offers the highest level of friction to guarantee perfect clutch operation in the three phases: starting, acceleration and maximum speed.

Reduced phosphorus and sulphur content, optimised (according to jaso MA2 < 1200 ppm) to ensure the operation and durability of exhaust catalysts.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	10W-40	FREEZING POINT:	-30°C / -22 F
DENSITY AT 15°C:	0.868	FLASHPOINT:	240°C / 264 F
VISCOSITY AT 100°C:	14.4 mm ² /s		
VISCOSITY AT 40°C:	100 mm ² /s		
VISCOSITY INDEX:	148		

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidio por 2016-2019

