



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

BRAKE FLUID DOT-4

Universal brake fluid

DESCRIPTION

A universal brake fluid for all braking (disk or drum) and clutch systems for motorcycles and cars.

PERFORMANCE

STANDARDS: FM VSS 116 DOT 3 / DOT 4
ISO 4925 (4 & 3)
SAE J1704

A synthetic fluid for disk or drum brake systems, and clutch controls where manufacturers require the standards indicated below. Particularly recommended due to its high boiling point, for passenger cars, motorcycles, trucks, coaches, public works machinery, etc.

- A very high performance fluid.
- Absolute safety in operation: immediate response in intensive use.
- Miscible in all proportions with fluids that meet the same standards.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

DENSITY AT 15°C:	1.050	BOILING POINT (dry):	260°C / 500 F
VISCOSITY AT -40°C:	< 1500 mm ² /s	BOILING POINT (damp):	160°C / 320 F

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidio por 2016-2019

