



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

BRAKE FLUID DOT-5.1

Universal brake fluid

DESCRIPTION

100% synthetic brake fluid for clutches and hydraulic braking systems of light and heavy vehicles, motorcycles and some new-generation bicycles.

PERFORMANCE

STANDARDS:

FM VSS 116 DOT 3 / DOT 4 / DOT 5.1 (without silicone base)
ISO 4925 (4 & 3)
SAE J1704

It is especially recommended for vehicles with ABS. Its high fluidity at low temperatures ensures rapid circulation to stability control systems and improves response time.

- A very high performance fluid.
- Absolute safety in operation: immediate response in intensive use.
- Miscible in all proportions with fluids that meet the same standards.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

DENSITY AT 15°C:	1.060	BOILING POINT (dry):	260°C / 500 F
VISCOSITY AT -40°C:	< 900 mm ² /s	BOILING POINT (damp):	180°C / 356 F

Rev.11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Lubricated since 1916

