



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

## **FORK FLUID 2.5 W**

### **Synthetic lubricant for forks**

#### **DESCRIPTION**

A synthetic fork lubricant designed to meet the demands of modern suspension systems from Kayaba, Showa, Ohlins, WP and any other kind. The exclusive additive protects joints, prolonging their life and reducing leaks.

#### **PERFORMANCE**

It does not produce varnish and does not clog the internal parts of the forks and hydraulic shock absorbers. It behaves excellently with respect to air due to its fast deaeration.

Reduced internal frictions particularly between the various tubes and joints.

High performance from the first stresses and maintained throughout the working time.

High-performance anti-foam, preventing air transfer and degassing of the pneumatic chamber in order to maintain the suspension's performance.

High anti-wear and extreme pressure properties.

Anti-corrosion and joint protection.

#### **CONDITIONS OF USE**

Maintenance interval as recommended by each manufacturer and adapted to its own use. Use the amount recommended by the manufacturer.

#### **TECHNICAL FEATURES**

<b>VISCOSITY AT 100°C:</b>	3.85 mm <sup>2</sup> /s	<b>FREEZING POINT:</b>	-40°C / -40 F
<b>VISCOSITY AT 40°C:</b>	13 mm <sup>2</sup> /s	<b>FLASHPOINT:</b>	170°C / 338 F
<b>VISCOSITY INDEX:</b>	210		

Rev. 11/23



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME  
Subsidio por 2016-2019

