



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GCC-10% LONG TIME

100% organic coolant

DESCRIPTION

100% organic, anti-freeze, all-weather coolant, specially formulated to be used in any type of cooling circuit, both sealed (C.C.) and open. The main purpose is to cool the engine and lower the freezing point of the water. Suitable for EURO VI vehicles.

PERFORMANCE

STANDARDS: ASTM D3306-00
J1034/91
UNE 26-361-88

It provides high operational stability, which means a long service life and therefore significant savings. Particularly suitable for cooling circuits and radiators made of aluminium or its alloys.

CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to your own use. No prior dilution required, ready-to-use product.

TECHNICAL FEATURES

COLOUR:	PINK / GREEN / YELLOW / BLUE	FREEZING POINT:	-4 °C / 24.8 °F
DENSITY:	1.017 gr/cm ³	FLASHPOINT (open):	103 °C / 217.4 °F
pH:	8	FLASHPOINT (closed):	112 °C / 233.6 °F

Rev.11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Lubricated since 1968

