



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL ATF III LONG LIFE

Lubricant for automatic transmissions

DESCRIPTION

A special, synthetic-based lubricant for torque converter transmissions, automatic gearboxes, power steering, etc. requiring a lubricant that meets the General Motors Dexron III specification.

PERFORMANCE

SPECIFICATIONS:

Allison C-4
GM Dexron II-D / Dexron III-H / Type A
MB 236.1
ZF TE-ML 09 / 11 / 14

- Excellent power transmission.
- High anti-wear ability.
- Long service life with great resistance to ageing and sludge formation.
- Optimised resistance to oxidation thanks to its synthetic base.
- High viscosity index, suitable for systems with large temperature variations.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

DENSITY AT 15°C:	0.875	FREEZING POINT:	-50°C / -58 F
VISCOSITY AT 40°C:	34 mm ² /s	FLASHPOINT:	210°C / 410 F
VISCOSITY INDEX:	205		

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidio por 2016-2019

