



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

# GLOBAL ATF III

## Lubricant for automatic transmissions

### DESCRIPTION

Especially suitable for all types of automatic or semi-automatic transmissions, torque converters and hydraulic systems where the manufacturer requires a GM Dexron III type automatic transmission fluid.

### PERFORMANCE

#### SPECIFICATIONS:

- Allison C-4 / TES 389
- Caterpillar TO-2
- Chrysler MS 9602 / MS 7176
- Ford WSS M2C 138-CJ / 166-H
- Dexron III-H / G / F / E / D
- Man 339 Z1 / Z2 / V2
- MB 236.1 / 236.6 / 236.7 / 236.9
- Voith 555.6335 / 556336
- Volvo 97340 / 97341
- ZF TE-ML 02F / 03D / 04D / 09 / 11A / 11B / 14A / 14B / 16L / 17C

- Excellent thermal stability thanks to its high antioxidant and detergent ability.
- Excellent friction properties that allow a controlled sliding of the friction elements.
- Smooth clutch operation, no excessive slippage and no jerky operation.
- Precision and control in the automatic gearbox, even in low-speed manoeuvres.
- Excellent fluidity at low temperatures to avoid sudden movements and overloading of circuits on cold start.

### CONDITIONS OF USE

Consult the vehicle maintenance manual before using the product. Oil changes must be made in accordance with the manufacturer's recommendations.

### TECHNICAL FEATURES

<b>COLOUR:</b>	Red	<b>FREEZING POINT:</b>	-45°C / -49 F
<b>DENSITY AT 15°C:</b>	0.860	<b>FLASHPOINT:</b>	210°C / 410 F
<b>VISCOSITY AT 100°C:</b>	7.5 mm <sup>2</sup> /s		
<b>VISCOSITY AT 40°C:</b>	34 mm <sup>2</sup> /s		
<b>VISCOSITY INDEX:</b>	149		

Rev.11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

