



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL ATF II

Lubricant for automatic transmissions

DESCRIPTION

Fluid for mechanical transmissions, torque converters, power steering and hydraulic circuits in which the manufacturer recommends the General Motors ATF Dexron IID or Ford Mercon standards and for ZF automatic gearboxes that are fitted to most European vehicles.

PERFORMANCE

For all kinds of vehicles.

- It exceeds the requirements of all manufacturers.
- It prevents swelling, hardening and cracking of seals.
- High resistance to oxidation.
- Specially formulated for a uniform and smooth transmission.
- It keeps transmissions free of varnish and deposits
- Anti-foam.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

COLOUR:	Red	FREEZING POINT:	-45°C / -49 F
DENSITY AT 15°C:	0.860	FLASHPOINT:	210°C / 410 F
VISCOSITY AT 100°C:	7.9 mm ² /s		
VISCOSITY AT 40°C:	39 mm ² /s		
VISCOSITY INDEX:	149		

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidized per 176/2012

