



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

# GLOBAL DRILL 100

## Lubricant for pneumatic tools

### DESCRIPTION

An oil manufactured from selected paraffin bases and additives for optimal performance in the applications for which it is intended.

### PERFORMANCE

**STANDARDS:** ISO 6743 / 11  
PAC and PBC

An extreme pressure oil for lubricating mechanisms in pneumatic tools, such as drills and hammers, even in severe working conditions.

Any non-desiccated air-actuated mechanism where oil lubrication is required.

- Excellent anti-wear and EP properties to guarantee long tool life.
- High capacity to emulsify the water carried by the air, avoiding its corrosive and wear action.
- Good anti corrosive and anti-rust properties in a wide range of temperatures.
- Excellent thermal stability and oxidation resistance, reducing deposit formation and increasing oil life.
- High adhesiveness.

### CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

### TECHNICAL FEATURES

<b>DENSITY AT 15°C:</b>	0.890	<b>FREEZING POINT:</b>	-15°C / 5 F
<b>VISCOSITY AT 40°C:</b>	100 mm <sup>2</sup> /s	<b>FLASHPOINT:</b>	250°C / 482 F
<b>VISCOSITY INDEX:</b>	>99	<b>WELD LOAD:</b>	315 Kg

Rev. 11/23



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME  
Lubricantes por 70 años

