



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

# GLOBAL SPECIAL 10W40

## Synthetic lubricant for light vehicles

### DESCRIPTION

A lubricant designed with synthetic and mineral components of a very high quality for passenger car and van diesel and petrol engines.

### PERFORMANCE

**STANDARDS:** ACEA A3 / B4  
API SL

**SPECIFICATIONS:** MB 229.1  
VW 501 01 / 505 00

For all types of diesel and petrol engines, both supercharged and atmospheric, where high speed regimes require a quality oil of great thermal stability. Lubricant for engines with direct injection system.

Its composition gives it high resistance to wear, corrosion and oxidation and provides high detergent and dispersant levels, allowing very long intervals between oil changes. Excellent cold starting at low temperatures. High detergent, dispersant, antioxidant capacity, minimising the formation of silt in the crankcase and avoiding the clogging of filters; great anti-wear ability prolonging the life of the engine.

### CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

### TECHNICAL FEATURES

<b>SAE VISCOSITY:</b>	10W-40	<b>FREEZING POINT:</b>	-30°C / -22 °F
<b>VISCOSITY AT 100°C:</b>	14.6 mm <sup>2</sup> /s	<b>FLASHPOINT:</b>	210°C / 410 °F
<b>VISCOSITY AT 40°C:</b>	110 mm <sup>2</sup> /s	<b>SULPHATED ASH:</b>	1.38 % Mass
<b>VISCOSITY INDEX:</b>	130	<b>TBN:</b>	11.5 mg KOH/g

Rev. 11/23



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

