



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

# GLOBAL SYNT 10W40

**High performance light vehicle synthetic lubricant**

## DESCRIPTION

A high-performance synthetic lubricant for four-stroke petrol and diesel engines, highly special, offering high lubricating film strength and withstanding great loads.

## PERFORMANCE

**STANDARDS:** ACEA A3 / B4  
API SN

**SPECIFICATIONS:** MB 229.3  
VW 502 00 / 505 00  
RN 0700 / 0710  
GM-LL-A / B 025  
B71 2300

Formulated with specially selected synthetic bases to provide superior wear protection to conventional oils, reducing friction and wear and improving engine cooling and performance.

Its high viscosity index allows an excellent cold start.

Better acceleration, reduced fuel consumption, longer engine life.

## CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

## TECHNICAL FEATURES

<b>SAE VISCOSITY:</b>	10W-40	<b>FREEZING POINT:</b>	-33°C / -27.4 F
<b>VISCOSITY AT 100°C:</b>	15 mm <sup>2</sup> /s	<b>FLASHPOINT:</b>	225°C / 437 F
<b>VISCOSITY AT 40°C:</b>	110 mm <sup>2</sup> /s	<b>SULPHATED ASH:</b>	1.32 % Mass
<b>VISCOSITY INDEX:</b>	150	<b>TBN:</b>	10.7 mg KOH/g

Rev. 11/23



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

