



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL SYNT 15W50

High performance light vehicle synthetic lubricant

DESCRIPTION

A high-performance synthetic lubricant for four-stroke petrol and diesel engines, highly special, offering high lubricating film strength and withstanding great loads.

PERFORMANCE

STANDARDS: ACEA A3 / B4
API SN

SPECIFICATIONS: MB 229.1

Formulated with specially selected synthetic bases to provide superior wear protection to conventional oils, reducing friction and wear and improving engine cooling and performance.

Its high viscosity index allows an excellent cold start.

Better acceleration, reduced fuel consumption, longer engine life.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	15W-50	FREEZING POINT:	-30°C / -22 F
VISCOSITY AT 100°C:	18 mm ² /s	FLASHPOINT:	225°C / 437 F
VISCOSITY AT 40°C:	150 mm ² /s	SULPHATED ASH:	1.32 % Mass
VISCOSITY INDEX:	133	TBN:	10.3 mg KOH/g

Rev.11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

