



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GMR 20W50

Multi grade lubricant for diesel and petrol engines

DESCRIPTION

Multi grade lubricant for turbocharged or atmospheric diesel and petrol engines under the most severe working conditions in: passenger cars, transport, public works machinery, agriculture, generators, static engines, marine diesel engines.

PERFORMANCE

STANDARDS: ACEA A3 / B4
API SL

- Great thermal stability.
- It avoids residue, varnish deposits and sludge.
- Very low ash content.
- It avoids lining polishing.
- Excellent anti-wear ability.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	20W-50	FREEZING POINT:	-24°C / -11.2 F
VISCOSITY AT 100°C:	18.4 mm ² /s	FLASHPOINT:	250°C / 482 F
VISCOSITY AT 40°C:	147 mm ² /s	SULPHATED ASH:	1.16 % Mass
VISCOSITY INDEX:	135	TBN:	9.6 mg KOH/g

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

