



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

# **GRO HYDRAULIC HV 46**

## **Micro-filtered hydraulic lubricant**

### **DESCRIPTION**

Refined and micro-filtered hydraulic lubricant to be used in systems subject to large temperature changes, and where anti-wear, oxidation stability and good corrosion resistance are required.

### **PERFORMANCE**

#### **STANDARDS:**

DIN 51524 part 3 (HVLP)  
Denison HF-0 / HF-1 / HF-2  
Vickers M-2950-S / I-286-S  
USS 127-136  
Cincinnati machine P-70  
AFNOR NF E 48-602 HV  
AFNOR NF E 48-603 HV

Some of its applications are:

- Public works and forest machinery.
- Forklift trucks working indoors and out.
- Numerical control machine tools, etc.
- High viscosity index
- Micro-filtered to 5 microns (class NAS 8/9)
- Excellent performance in pumping systems at all speeds
- Compatible with all kinds of steels and bronzes
- It does not attack seals
- It protects against corrosion
- High desemulsivity index.
- Rapid water separation.

Rev.06/24



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME  
Subsidio por 2016-2019



