



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GRO HYDRAULIC HV 68

Micro-filtered hydraulic lubricant

DESCRIPTION

Refined and micro-filtered hydraulic lubricant to be used in systems subject to large temperature changes, and where anti-wear, oxidation stability and good corrosion resistance are required.

PERFORMANCE

STANDARDS:

DIN 51524 part 3 (HVLP)
Denison HF-0 / HF-1 / HF-2
Vickers M-2950-S / I-286-S
USS 127-136
Cincinnati machine P-70
AFNOR NF E 48-602 HV
AFNOR NF E 48-603 HV

Some of its applications are:

- Public works and forest machinery.
- Forklift trucks working indoors and out.
- Numerical control machine tools, etc.
- High viscosity index
- Micro-filtered to 5 microns (class NAS 8/9)
- Excellent performance in pumping systems at all speeds
- Compatible with all kinds of steels and bronzes
- It does not attack seals
- It protects against corrosion
- High desemulsivity index.
- Rapid water separation.

Rev.06/24



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidio por 2016-2017





PERFORMANCE LUBRICATION

PRODUCT INFORMATION

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

ISO VISCOSITY:	68	FREEZING POINT:	-24°C / -11.2 F
DENSITY AT 15°C:	0.860	FLASHPOINT:	230°C / 446 F
VISCOSITY AT 100°C:	11.02 mm ² /s		
VISCOSITY AT 40°C:	68 mm ² /s		
VISCOSITY INDEX:	153		

Rev.06/24



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidio por 2016-2022

