



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

# **GRO MULTISPRAY PTFE**

## **Multifunctional lubricant with PTFE**

### **DESCRIPTION**

A multifunctional lubricant with a special base and polytetrafluoroethylene (PTFE) with a formula based on oils, solvents and additives that give it great ability to lubricate, penetrate and protect. It has highly lubricating properties, achieving an optimal result in the lubrication of all types of mechanical joints, reducing friction and eliminating noise.

An excellent product against moisture displacement. Reaching the most inaccessible places, lubricating and protecting from corrosion. It protects and extends the use of all types of mechanisms and metal parts.

### **PERFORMANCE**

Lubricant for small moving parts.

- Protector against corrosion, even metal parts exposed to the weather.
- It eliminates noise and softens all kinds of articulations.
- It facilitates the assembly of bolts, nuts and seized parts.
- Moisture displacement.
- It does not damage plastic, rubber and ceramic components.

### **CONDITIONS OF USE**

- Before the first application, clean and degrease the surfaces to be treated.
- Shake vigorously before use.
- Keep the bottle upright, both during storage and when using it.

### **TECHNICAL FEATURES**

<b>DENSITY AT 15°C:</b>	0.847 g/cm <sup>3</sup>
<b>VISCOSITY AT 40°C:</b>	46 mm <sup>2</sup> /s
<b>FREEZING POINT:</b>	-33°C / -27.4 F
<b>FLASHPOINT:</b>	210°C / 410 F

Rev. 11/23



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME  
Lubricant por 196.102

