



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

## GS-3 TDI 15W40

**Multi grade lubricant for light petrol and diesel engines**

### DESCRIPTION

Excellent performance under the most severe working conditions in: passenger cars, transport, public works machinery, agriculture, generators, static engines, marine diesel engines.

### PERFORMANCE

**STANDARDS:** API CF-4

**SPECIFICATIONS:** MB 228.1  
MAN 271  
MTU Type-1

- Great thermal stability.
- It avoids residue, varnish deposits and sludge.
- Very low ash content.
- It avoids lining polishing.
- Excellent anti-wear ability.

### CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

### TECHNICAL FEATURES

<b>SAE VISCOSITY:</b>	15W-40	<b>FREEZING POINT:</b>	-27°C / -16.6 F
<b>VISCOSITY AT 100°C:</b>	14.4 mm <sup>2</sup> /s	<b>FLASHPOINT:</b>	225°C / 437 F
<b>VISCOSITY AT 40°C:</b>	115 mm <sup>2</sup> /s	<b>SULPHATED ASH:</b>	1.10 % Mass
<b>VISCOSITY INDEX:</b>	125	<b>TBN:</b>	7.5 mg KOH/g

Rev.11/23



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME  
Subsidio por 2016-2019

