



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GXS ULTRA+ 5W50

100% synthetic lubricant for light vehicles

DESCRIPTION

A 100% synthetic high-performance lubricant that offer the best possible performance and protection in the automotive lubricant sector.

Formulated with special synthetic bases and tri-ester technology, to achieve the highest performance. The final result is a lubricant with incomparable anti-wear properties with maximum efficiency in a wide range of temperatures.

PERFORMANCE

STANDARDS: ACEA A3 / B4
API SN

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use. Some engines **cannot** use this type of lubricant. Before using it consult the vehicle maintenance book...

TECHNICAL FEATURES

SAE VISCOSITY:	5W-50	FREEZING POINT:	-50°C / -58 F
VISCOSITY AT 100°C:	17 mm ² /s	FLASHPOINT:	240°C / 464 F
VISCOSITY AT 40°C:	104 mm ² /s	SULPHATED ASH:	1 % Mass
VISCOSITY INDEX:	179	TBN:	9.5 mg KOH/g

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

