



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

HYDRAULIC HLP-32

Micro-filtered hydraulic lubricant

DESCRIPTION

Fluid for hydraulic circuits for forklift trucks and hydraulic lifters, public works machinery, agricultural machinery, machine tools, presses and injection machines.

PERFORMANCE

STANDARDS: ISO 6074 (HM)
DIN 51524, part 2 (HLP)
AFNOR NF E 48-602 HM
AFNOR NF E 48-603 HM

- Refined oil micro-filtered to 5 microns.
- High viscosity index (excellent response to temperature changes).
- Anti-corrosive ability, excellent resistance to oxidation.
- High resistance to ageing
- Compatible with viton, rubber or any type of synthetic gaskets.
- Anti-foam properties.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

ISO VISCOSITY:	32	FREEZING POINT:	-21°C / -5.8 F
DENSITY AT 15°C:	0,860	FLASHPOINT:	235°C / 455 F
VISCOSITY AT 100°C:	5.4 mm ² /s		
VISCOSITY AT 40°C:	32 mm ² /s		
VISCOSITY INDEX:	100		

Rev.06/24



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidio por 2016-2017

