



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

KART 2

100% synthetic lubricant for karts

DESCRIPTION

A 100% synthetic lubricant for 2-stroke petrol engines, highly special, offering high lubricating film strength and withstanding great loads. Its synthetic structure ensures maximum protection in very harsh competitive conditions.

PERFORMANCE

STANDARDS: API TC
 JASO FD
 ISO L-EGD

Outstanding film strength and stress-bearing capabilities, ensuring trouble-free operation under extreme conditions. It incorporates a sophisticated chemical dispersant system that ensures the engine stays clean. This special base blend of synthetic hydrocarbon and ester results in fewer deposits during combustion. Thanks to this residue-free combustion, the exhaust and combustion chamber are kept at their initial volumes, maintaining engine performance and avoiding run-on caused by incandescent residue; the segments remain free in their seats, thus ensuring the perfect sealing of the combustion chamber and therefore the engine's compression ratio.

CONDITIONS OF USE

For optimum performance 2% is recommended for most engines. Follow the engine manufacturer's instructions.

TECHNICAL FEATURES

DENSITY AT 15°C:	0.900	FREEZING POINT:	-25°C / -13 F
VISCOSITY AT 100°C:	16 mm ² /s	FLASHPOINT:	235°C / 455 F
VISCOSITY AT 40°C:	125 mm ² /s	COLOR:	Red
VISCOSITY INDEX:	140		

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidado por 2016-2022

