



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

ORIGIN RBSO-2AE 0W20

100% synthetic light vehicle lubricant

DESCRIPTION

High performance 100% synthetic fuel economy" lubricant, specially designed for latest generation Volvo "DRIVE-E" petrol (VEP) and diesel (VED) engines equipped with catalytic converters and particulate filters (DPF).

PERFORMANCE

STANDARDS: ACEA C5
API SN

SPECIFICATIONS: Volvo VCC RBSO-2AE

Fuel-efficient engine lubricant (SAE 0W20), developed according to the latest technology, based on specially selected synthetic base oils and a well-balanced selection of additives to achieve the following properties:

- High fuel economy.
- High and stable viscosity index.
- Good shear resistance.
- Very fast cold start, even at very low temperatures.
- Reliable lubrication film at very high temperatures.
- Very good detergency and dispersing power.
- Very good protection against wear, corrosion and foaming.

A specially formulated fuel-saving engine oil, suitable for Volvo petrol and diesel engines when the manufacturer prescribes a product that meets the VCC RBSO-2AE specification with SAE 0W20 viscosity.

The latest generation Volvo engines of the VEA (4-cylinder) type, both petrol and diesel, require a very specific lubricant as they are engines for small and light vehicles. The VCC RBSO-2AE standard is particularly demanding on fuel economy performance and associated with the ACEA C5 standard for lubricants.

Rev.11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.





PERFORMANCE LUBRICATION

PRODUCT INFORMATION

CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	0W-20	FREEZING POINT:	-48 °C / -54.4 °F
DENSITY AT 15 °C:	0.847	FLASHPOINT:	220 °C / 428 °F
VISCOSITY AT 100 °C:	8.70 mm ² /s	SULPHATED ASH:	0.80 % Mass
VISCOSITY AT 40 °C:	45.90 mm ² /s	TBN:	7.7 mg KOH/g
VISCOSITY INDEX:	173		

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subvenció per 2016-2020

