



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

# SCOOTER 4T 10W40

## Synthetic lubricant for scooter

### DESCRIPTION

A synthetic-based lubricant specially designed for old and modern Scooters and Maxi Scooters, equipped with 4-stroke engines, all engine sizes, with or without post-catalytic systems.

All scooters used in urban and intercity travel.

### PERFORMANCE

**STANDARDS:** API SL  
JASO MA

Formulated with special additives that give it high chemical stability and resistance to oxidation. With a high detergent ability, it keeps the engine clean and free of carbon deposits. Its high fluidity allows quick starts even at low temperatures.

The jaso MA specification offers an excellent level of friction to ensure wet clutch friction and longevity. Excellent resistance of the lubricating film for high temperature protection, particularly suitable for long periods at full load with continuous stopping and starting and accompanied by difficult cooling.

Low volatility to limit oil consumption as much as possible.

### CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

### TECHNICAL FEATURES

<b>SAE VISCOSITY:</b>	10W-40	<b>FREEZING POINT:</b>	-33°C / -27.4 F
<b>VISCOSITY AT 100°C:</b>	15 mm <sup>2</sup> /s	<b>FLASHPOINT:</b>	225°C / 437 F
<b>VISCOSITY AT 40°C:</b>	110 mm <sup>2</sup> /s		
<b>VISCOSITY INDEX:</b>	150		

Rev. 11/23



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME  
Subsidized per 2016 2019

