



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

SCOOTER OIL 2T

Synthetic lubricant for 2-stroke engines

DESCRIPTION

A synthetic premix or injection lubricant for 2-stroke Scooter engines equipped with automatic greasing systems.

PERFORMANCE

STANDARDS: API TC
JASO FC

A new formula adapted to the new generation of scooters and urban motorcycles of medium and small engine size with premix system or separate tank. Minimal formation of smoke and carbon deposits lengthens the life of the spark plugs.

- Minimum smoke emission. It reduces pollution.
- Better combustion and greater cleaning.
- No carbon accumulation.
- It maintains optimum engine performance.
- Reduced maintenance costs.
- It reduces friction and extends the engine's useful life.
- Quick starting.
- Anti-wear properties provide longer engine life.

TECHNICAL FEATURES

| | | | |
|----------------------------|------------------------|------------------------|-----------------|
| COLOUR: | Blue | FREEZING POINT: | -32°C / -25.6 F |
| DENSITY AT 15°C: | 0.871 | FLASHPOINT: | 108°C / 226.4 F |
| VISCOSITY AT 100°C: | 8.9 mm ² /s | | |
| VISCOSITY AT 40°C: | 60 mm ² /s | | |
| VISCOSITY INDEX: | 100 | | |

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Lubricant por 7 años 2015



ISO 9001
ISO 14001
BUREAU VERITAS
Certified