



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

SPIRIT 20W50

Mineral lubricant for 4-stroke motorcycle engines

DESCRIPTION

A mineral-based lubricant formulated for all types of motorcycles... 4-stroke engines, with or without integrated gearboxes and oil-bathed or dry clutch, engines designed to use high viscosity lubricants, which meet euro 2, 3, 4 and 5 anti-pollution standards equipped with exhaust gas treatment systems such as catalyts, air injection in the exhaust.

Particularly recommended for Harley-Davidson, which recommend an SAE 20W-50 grade oil.

PERFORMANCE

STANDARDS: API SN
JASO MA2

The jaso MA2 standard offers the highest level of friction to guarantee perfect clutch operation in the three phases: Starting, acceleration and maximum speed.

Reduced phosphorus and sulphur content, optimised (according to jaso MA2 < 1200 ppm) to ensure the operation and durability of exhaust catalyts.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use. Always consult your vehicle maintenance book before use.

TECHNICAL FEATURES

SAE VISCOSITY:	20W-50	FREEZING POINT:	-25°C / -13 F
VISCOSITY AT 100°C:	18.7 mm ² /s	FLASHPOINT:	250°C / 482 F
VISCOSITY AT 40°C:	159 mm ² /s		
VISCOSITY INDEX:	130		

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidio por 2016-2019

