



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

TRANS SYNT 10W40

Synthetic lubricant for motorcycle gearboxes

DESCRIPTION

Specially designed for these applications, it is a high performance oil in all aspects of clutch and gearbox lubrication offering the ultimate in transmission and cardan shaft protection.

PERFORMANCE

STANDARDS: JASO MA.

RECOMMENDATIONS: Designed for Honda, Yamaha, Suzuki, etc. transmissions.

Contains Extreme Pressure additives that absorb the heavy impact loads frequently encountered in transmissions, especially during gear shifting and acceleration and deceleration. The extreme resistance of its film avoids metal to metal contact on gear teeth. Its high power translates into less friction, lower wear and reduced temperature. This means more efficient power transmission and longer life.

Very stable to shear breakage and prevents rapid destruction of additives. In addition, it has extremely high thermal stability, which allows it to resist breakage well and prevent foaming.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	10W-40	FREEZING POINT:	-27 °C / -16,6 °F
DENSITY AT 15 °C:	0.865	FLASHPOINT:	220 °C / 428 °F
VISCOSITY AT 100°C:	14.5 mm ² /s	TEST 4 EP BALLS (welding):	315 Kg
VISCOSITY AT 40°C:	105 mm ² /s		
VISCOSITY INDEX:	142		

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidio por 2019-2022

