



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GCC LONG TIME PURO

PURE ANTIFREEZE

DESCRIPTION

A 100% organic coolant, specially formulated to be used in any type of cooling circuit, both sealed and open. Its basic mission is to cool the engine and lower the freezing point of water. Suitable for euro VI vehicles.

PERFORMANCE

STANDARDS:

UNE 26361.88
ASTM D-3306 / 4985
SAE J1034
NATO S-759

SPECIFICATIONS:

VW TL 774-D (G12) / TL 774-F (G12+)
MB 325.3
Man 324
Renault 41-01-001
Ford WSS M97 B44-C / B49-A
Chrysler MS 9176 / MS 12106
Cummins 90T8-4
Wärtsila 32-9011
Leyland trucks LTS 22 AF10
GM 1899M

Great stability in service, meaning long life and significant savings. It is especially recommended for aluminium or aluminium alloy cooling circuits and radiators in light or heavy vehicles, allowing the concentration of the solution to be adjusted according to the required freezing point.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use. A product to mix with distilled water, **not to be used** with cloudy or hard waters.

Rev.11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidial por 2016-2019





PERFORMANCE LUBRICATION

PRODUCT INFORMATION

TECHNICAL FEATURES

COLOUR:	Yellow	BOILING POINT (open):	197°C / 386.6 F
DENSITY AT 15°C:	1.115	BOILING POINT (closed):	220°C / 428 F
pH:	8		

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidizado por 2016-2022

