



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

UNIVERSAL 4T SAE 15W40

Multigrade lubricant for gardening

DESCRIPTION

Multigrade oil for all kind of engines 4T. High thermal stability avoiding residue and sludge formation, detergency and dispersant power. Excellent antioxidant, antirust and antifoaming properties.

PERFORMANCE

STANDARDS: API SG

It presents great thermal stability, maintaining its initial properties even when working under extreme conditions and prolonging the periods of change.

Extraordinary resistance to the formation of residues and deposition of silt and varnishes.

A multigrade, it facilitates engine start-up and provides excellent lubrication in cold and hot conditions.

Thanks to its high anti-friction ability and anti-wear additives, it prevents liner polishing, keeps the engine in perfect operation and minimises fuel consumption.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	15W-40	FREEZING POINT:	-27°C / -16.6 F
VISCOSITY AT 100°C:	15 mm ² /s	FLASHPOINT:	226°C / 438.8 F
VISCOSITY AT 40°C:	115 mm ² /s	TBN:	7 mg KOH/g
VISCOSITY INDEX:	135		

Rev. 11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME

Subsidio por 2016-2017



ISO 9001
ISO 14001
BUREAU VERITAS
Certified

