



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

FACTORY 10W50

100% synthetic Tri-Ester based lubricant

DESCRIPTION

A 100% synthetic high performance lubricant developed with Tri-Ester technology to be used in any 4-stroke engine seeking maximum performance.

Formulated with exclusive bases and specially selected additives, it is recommended for both competition and road engines subject to great stress and high operating temperatures. Under these conditions, it helps to reduce the internal wear of the different components of the engine thanks to the protective film of lubricant that it leaves on each component.

It helps improve performance due to its low viscosity, which directly results in low internal friction, maintaining optimal pressure in the lubrication system

PERFORMANCE

STANDARDS: Developed for competition engines

The 100% synthetic base provides exceptional oil film shear resistance at high temperatures and high engine speeds.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	10W-50	FREEZING POINT:	-40°C / -40 F
VISCOSITY AT 100°C:	19 mm ² /s	FLASHPOINT:	225°C / 437 F
VISCOSITY AT 40°C:	120 mm ² /s	COLOR:	Fluorescent yellow
VISCOSITY INDEX:	179		

Rev. 03/24



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

