



PERFORMANCE LUBRICATION

INFORMACIÓN DEL PRODUCTO

GLOBAL ATF-CVT

Synthetic lubricant for Continuously Variable Transmission (CVT) chain and belt drives

DESCRIPTION

High performance synthetic lubricant, specially designed for Continuous Variable Transmission (CVT) gearboxes.

Recommended for the vast majority of vehicles equipped with CVT, both belt CVT and chain CVT. Particularly suitable for CVT gearboxes from American manufacturers GM, FORD, CHRYSLER..., Asian manufacturers HONDA, HYUNDAI, KIA, MITSUBISHI, TOYOTA, NISSAN, SUBARU, TOYOTA..., or European manufacturers AUDI, BMW, CITROËN, MERCEDES, PEUGEOT, RENAULT,...

Caution: Not applicable to CVT systems on hybrid vehicles.

BENEFITS

SPECIFICATIONS: See attached table

100% synthetic high-tech lubricant, suitable for use in most CVTs, both for both chain and belt CVT systems.

Thanks to its formulation, the product provides:

- Reduces fuel consumption in CVT-equipped vehicles by optimising metal-to-metal friction between belt or chain and pulleys.
- It provides a smoother and faster speed step.
- Improved cold operation of CVT automatic gearboxes.
- Increased service life due to increased oxidation resistance and oil film stability at high temperatures.
- Increased wear protection for chains, belts and pulleys.
- Anti-corrosion, Anti-foam.

Rev. 02/24



www.globalracingoil.com

Compañía General de Lubricantes, S.A. se reserva el derecho de modificar las características generales que aparecen en este documento, hasta el momento en que el cliente formule su pedido, sometido a nuestras condiciones generales de venta y garantía.





PERFORMANCE LUBRICATION

INFORMACIÓN DEL PRODUCTO

CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

TECHNICAL CHARACTERISTICS

DENSITY AT 15°C:	0,850 g/ml	VISCOSITY INDEX:	180
VISCOSITY AT 100°C:	7,2 mm ² /s	FREEZING POINT:	<-40 °C / <-40 °F
VISCOSITY AT 40°C:	34,3 mm ² /s	FLASH POINT:	210 °C / 410 °F

OEM SPECIFICATIONS

AUDI	G 052 180, G 052 516, Multitronic, TL 52 116, TL 52 180, TL 52 516
BMW	83 22 0 136 376, 83 22 0 429 154, EZL 799, EZL 799 A
CHRYSLER	CVTF+4, NS-2
CITROËN	9735 EF, Elfmatic CVT, Elfmatic CVT MV
DODGE	05191184AA, CVTF+4, NS-2
DS	9735 EF, Elfmatic CVT, Elfmatic CVT MV
FIAT	Guardianship Car CVT N.G
FORD	CVT23, CVT30, MERCON C, WSS-M2C928-A, WSSM2C933-A, XT-7QCFT
GENERAL MOTORS	1940713, 1940714, DEX-CVT
HONDA	08200-9006, 08200-HCF-2, 0826099905HE, 087009006, HMMF (Honda Multi Matic Fluid) for CVT models only, without wet starting clutch, CVT-F, Genuine CVT Fluid, HCF-2, Z-1 (CVT models only, without starting clutch, not for Honda Jazz & Fit MY 2001-2007)
HYUNDAI	CVT-1, Genuine CVTF, SP-CVT 1, SP III (CVT models only)
INFINITI	NS-1, NS-2, NS-3
JEEP	05191184AA, CVTF+4, NS-2, VTF
KIA	CVT-1, SP-CVT 1, SP III (CVT models only)
LEXUS	CVTF 3320, CVT FE, Fluid FE, Fluid TC
MAZDA	CVTF 3320, JWS 3320
MERCEDES-BENZ	A 001 989 46 03, MB 236.20
MG	EM-CVTF
MINI	83 22 0 136 376, 83 22 0 429 154, COOPER EZL 799 A, EZL 799, ZF CVT V1
MITSUBISHI	CVTF ECO J4, Dia Queen CVTF-J1 (MMC Diaqueen CVT Fluid J1), Dia Queen CVTF-J4, Dia Queen CVTF-J4+ (MMC Diaqueen CVT Fluid J4 and J4+), MZ313973, SP III (CVT models only)
NISSAN	999MP-NS200P, KTF-1, N-CVT, NS-1, NS-2, NS-2V, NS-3
PEUGEOT	9735 EF, Elfmatic CVT, Elfmatic CVT MV
RENAULT	CVT CK/SK/FK, Elfmatic CVT, Elfmatic CVT MV
ROVER	EM-CVTF, Unipart Transmatic ATF
SEAT	G 052 180, G 052 516
SUBARU	CV30, CVT III Fluid, CVT TR580, CVT TR690, ECVT, High Torque CVT, iCVTF, i-CVTF FG, K0421Y0700, K0425Y0710, K0425Y0711, Lineartronic chain CVT 3 Fluid, Lineartronic chain CVT and CVT II Fluid, Lineartronic CVTF, Lineartronic High Torque (HT) CVT Fluid, Lineartronic II, NS-2
SUZUKI	CVTF 3320, CVTF 4401, CVTF TC, CVTF Green 1, CVTF Green 1V, CVTF Green 2, NS-2
TOYOTA	CVTF 3320, CVTF FE, TC
VOLVO	CVTF 4959
VOLKSWAGEN	G 052 180, G 052 516

PRODUCTS

ELF	matic CVT, matic CVT MV
ESSO	EZL 799, FN1975
MOBIL	CVTF 3320
MOPAR PARTS	CVTF+4, CVTplus4
SHELL	Green 1V

Rev. 02/24



www.globalracingoil.com

Compañía General de Lubricantes, S.A. se reserva el derecho de modificar las características generales que aparecen en este documento, hasta el momento en que el cliente formule su pedido, sometido a nuestras condiciones generales de venta y garantía.

