



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

## GEAR LUBE EP 75W80

**Lubricant for manual transmissions and differentials**

### DESCRIPTION

An extreme-pressure lubricant for gearboxes, highly loaded hypoid gear bridges, gearings and other mechanical transmission components.

### PERFORMANCE

**STANDARDS:** API GL-4 / GL-5

**SPECIFICATIONS:** MT-1  
Mack GO-J  
ZF TE-ML 08

The lube contains extreme pressure additives that absorb the heavy shock loads that are common in transmissions, especially in gear changes and during acceleration and deceleration. The extreme resistance of its film prevents metal-to-metal contact in the gear teeth, reducing friction and temperature. This means more efficient power transmission and longer life.

### CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

### TECHNICAL FEATURES

<b>SAE VISCOSITY:</b>	75W-80	<b>FREEZING POINT:</b>	-38 °C / -36.4 F
<b>VISCOSITY AT 100°C:</b>	9.5 mm <sup>2</sup> /s	<b>FLASHPOINT:</b>	230°C / 446 F
<b>VISCOSITY AT 40°C:</b>	70 mm <sup>2</sup> /s	<b>4-BALL TEST:</b>	315
<b>VISCOSITY INDEX:</b>	114		

Rev. 02/25



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

