



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GEAR LUBE EP 85W90

Lubricant for manual transmissions and differentials

DESCRIPTION

An extreme-pressure mineral lubricant for gearboxes, highly loaded hypoid gear bridges, gearings and other mechanical transmission components.

PERFORMANCE

STANDARDS: API GL-5

SPECIFICATIONS: MIL PRF-2105 D
ZF TE-ML 07 A

The lube contains extreme pressure (EP) additives that absorb the heavy shock loads that are common in transmissions, especially in gear changes and during acceleration and deceleration. The extreme resistance of its film prevents metal-to-metal contact in the gear teeth, reducing friction and temperature. This means more efficient power transmission and longer life.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY: 85W-90

DENSITY AT 15°C: 0.880

VISCOSITY AT 100°C: 17 mm²/s

VISCOSITY AT 40°C: 185 mm²/s

VISCOSITY INDEX: > 100

FREEZING POINT: -30°C / -22 F

FLASHPOINT: 250°C / 482 F

Rev. 02/25



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

