



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GEAR LUBE EP 90

Lubricant for manual transmissions

DESCRIPTION

Valvoline formulated with a mineral oil base and special additives to improve its performance against high pressures, high temperatures and high speeds. Recommended for gears, transmissions and gearboxes.

PERFORMANCE

STANDARDS: API GL-4
USS STEEL 224

- Excellent additives stability with temperature, lengthening the change periods, with less residue formation and greater protection of the mechanical components.
- Good anti-foaming, anti-corrosive and anti-oxidant properties to preserve optimal lubrication even against with contaminants such as air and water in the oil.
- High anti-wear and load-bearing capacity, preventing premature wear due to shock loads and intensive use.
- High viscosity index, to minimise the effect of temperature on oil viscosity, ensuring the permanence of the lubricating oil film at high temperatures caused by intensive and/or continuous use.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	90	FREEZING POINT:	-18°C / -0.4 F
VISCOSITY AT 40°C:	225 mm ² /s	FLASHPOINT:	250°C / 482 F
VISCOSITY INDEX:	97		

Rev. 02/25



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidized by 70% I+D+i

