



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GEAR LUBE GL-4 80W90

Lubricant for manual transmissions

DESCRIPTION

An extreme-pressure mineral lubricant for gearboxes, highly loaded hypoid gear bridges, gears and other mechanical transmission components.

PERFORMANCE

STANDARDS: API GL-4

SPECIFICATIONS: ZF TE-ML 08

The lube contains extreme pressure (EP) additives that absorb the heavy shock loads that are common in transmissions, especially in gear changes and during acceleration and deceleration. The extreme resistance of its film prevents metal-to-metal contact in the gear teeth, reducing friction and temperature. This means more efficient power transmission and longer life.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	80W-90	FREEZING POINT:	-30°C / -22 F
DENSITY AT 15°C:	0.900	FLASHPOINT:	220°C / 428 F
VISCOSITY AT 100°C:	16.8 mm ² /s		
VISCOSITY AT 40°C:	180 mm ² /s		
VISCOSITY INDEX:	> 100		

Rev. 02/25



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

