



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GEAR LUBE INTARDER Z-4 75W80

Lubricant for manual transmissions

DESCRIPTION

100% synthetic lubricant for synchronised or non-synchronised mechanical gearboxes and specially adapted to ZF gearboxes with intarder.

PERFORMANCE

STANDARDS: API GL-4

SPECIFICATIONS: Man 341 Type E-3 / Z-4
ZF TE-ML 02L / 16K

Specially formulated for commercial vehicles, heavy vehicles and coaches equipped with ZF mechanical gearboxes and applications where an API GL-4 performance level is required. High viscosity index that allows an easy cold start. Extreme Pressure and anti-wear properties that ensure gear and synchroniser durability. Excellent anti-foam, anti-corrosion, anti-rust and oxidation resistance properties.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	75W-80	FREEZING POINT:	-39°C / -38.2 F
VISCOSITY AT 100°C:	9.83 mm ² /s	FLASHPOINT:	240°C / 464 F
VISCOSITY AT 40°C:	66.5 mm ² /s		
VISCOSITY INDEX:	131		

Rev. 02/25



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME

