



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

# GEAR SYNT 75W90

**Lubricant for manual transmissions and differentials**

## DESCRIPTION

Specially formulated for gears in which the special base oils and the highly proven additive technology combine to provide extraordinary performance and lubricating power.

## PERFORMANCE

**STANDARDS:** API GL-4 / GL-5

**SPECIFICATIONS:** MT-1  
Mack GO-J  
MB 235.8  
Ford WSS M2C 200-C

High thermal stability and antioxidant power that allow longer change intervals. Greater fluidity at low temperatures and great efficiency that produce significant fuel savings. It offers great advantages over conventional oils by considerably improving gearbox and differential efficiency, as well as achieving significant fuel savings (from 1.9 to 2.3%) and a 10% decrease in temperature.

## CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

## TECHNICAL FEATURES

<b>SAE VISCOSITY:</b>	75W-90	<b>FREEZING POINT:</b>	-45°C / -49 F
<b>VISCOSITY AT 100°C:</b>	15 mm <sup>2</sup> /s	<b>FLASHPOINT:</b>	200°C / 392 F
<b>VISCOSITY AT 40°C:</b>	110 mm <sup>2</sup> /s		
<b>VISCOSITY INDEX:</b>	142		

Rev. 02/25



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME  
Subsidado por 2016-2020

