



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

## GLOBAL ATF-HD

**100% synthetic lubricant for modern heavy duty automatic transmissions.**

### DESCRIPTION

100% synthetic lubricant specially designed for automatic transmissions.

modern heavy-duty vehicles, trucks, buses and coaches (manual mode, manual mode, manual mode, manual mode).

sequential transmissions, electronic controls...) with or without torque converter lock-up offer a long maintenance interval under very severe driving conditions and are fully adapted for continuous start/stop driving. Particularly recommended for use in ZF and Voith automatic transmissions: ZF Ecomat, ZF Ecolite, Voith H55.6335.

### BENEFITS

#### **SPECIFICATIONS:**

MAN Type 339 V2  
MAN Type 339 Z3  
MAN Type 339 Z12  
MB 236.9  
VOITH 150.014524.xx  
VOLVO 97341  
ZF TE-ML 14C (Ecomat)  
ZF TE-ML 20C (Ecolife)

Product advantages:

- Provides extended maintenance intervals due to increased resistance to oxidation and high temperature shear.
- It provides smooth, jolt-free operation and prevents vibrations at the flywheel.
- Protects the numerous, compact and highly loaded gears.
- Provides superior automatic gearbox response: smooth feel and minimises shifting time.
- Improves the reaction of the automatic gearbox at low temperatures.
- Anti-wear, anti-corrosion, anti-foam.

Rev. 02/25



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE GME

ESTABLISHED SINCE 1951





PERFORMANCE LUBRICATION

## PRODUCT INFORMATION

### CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

### TECHNICAL CHARACTERISTICS

<b>COLOUR:</b>	Amber	<b>FREEZING POINT:</b>	-42°C / -43.6 °F
<b>DENSITY AT 15°C:</b>	0.840	<b>FLASH POINT:</b>	220 °C / 428 °F
<b>VISCOSITY AT 100°C:</b>	7.2 mm <sup>2</sup> /s		
<b>VISCOSITY AT 40°C:</b>	37 mm <sup>2</sup> /s		
<b>VISCOSITY INDEX:</b>	160		

Rev. 02/25



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME

RECONOCIMIENTO

