



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GEAR SYNT LS 75W140

Lubricant for manual transmissions and differentials

DESCRIPTION

Specially formulated to be used in both gearboxes and differentials with limited slip (inappropriately called self-locking).

PERFORMANCE

STANDARDS: API GL-4 / GL-5 LS

SPECIFICATIONS: MT-1
Mack GO-J
MB 235.8
Ford WSS M2C 200-C

High thermal stability and antioxidant power that allow longer change intervals. Greater fluidity at low temperatures and great efficiency that produce significant fuel savings. It offers great advantages over conventional oils by considerably improving gearbox and differential efficiency, as well as achieving significant fuel savings (from 1.9 to 2.3%) and a 10% decrease in temperature.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	75W-140	FREEZING POINT:	-45°C / -49 F
VISCOSITY AT 100°C:	26 mm ² /s	FLASHPOINT:	240°C / 464 F
VISCOSITY AT 40°C:	185 mm ² /s		
VISCOSITY INDEX:	175		

Rev. 02/25



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidado por 2016-2019

