



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL FLEET CORE 10W-40

Multigrade lubricant for heavy diesel engines

DESCRIPTION

Multigrade lubricant for diesel engines, turbocharged and non-turbocharged, long life, in heavy duty vehicles: trucks, buses, public works machinery, etc.

BENEFITS

STANDARDS:

ACEA E7
API CI-4 / SL

SPECIFICATIONS:

JASO DH-1
GLOBAL DHD-1
DTFR 15B110 (MB 228.3)
MAN M3275-1
VOLVO VDS-3
REANULT RLD-2
MACK EO-N
CATERPILLAR CAT ECF-1a
MTU Type-2
CUMMINS CES 20078
DETROIT DIESEL DDC 93K215
DEUTZ DQC III-18

API CI-4 provides protection and durability for engines equipped with EGR:

- Dispersant and antioxidant properties: protection against viscosity increase in the presence of residues and filter clogging.
- Very high anti-wear power: protection against liner polishing.
- High detergent power: protects pistons and reduces piston deposits.

The cold viscosity grade significantly improves wear protection at start-up and saves fuel during frequent starts.

Anti-corrosion, anti-rust, anti-foam.

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.





PERFORMANCE LUBRICATION

PRODUCT INFORMATION

CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

TECHNICAL CHARACTERISTICS

<i>VISCOSITY SAE:</i>	10W-40	<i>FREEZING POINT:</i>	-30 °C / -22 °F
<i>VISCOSITY AT 100°C:</i>	15 mm ² /s	<i>FLASH POINT:</i>	225 °C / 437 °F
<i>VISCOSITY AT 40°C:</i>	110 mm ² /s	<i>SULPHATED ASHES:</i>	1,32 % Mass
<i>VISCOSITY INDEX:</i>	150	<i>TBN:</i>	10,3 mg KOH/g

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

