



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL FLEET CORE 15W-40

Multigrade lubricant for heavy diesel engines

DESCRIPTION

A multigrade lubricant for long-lasting diesel engines, turbocharged or not, in heavy vehicles: trucks, buses, public works machinery, etc.

PERFORMANCE

STANDARDS: ACEA E7
API CI-4 / SL

SPECIFICATIONS: JASO DH-1
GLOBAL DHD-1
DTFR 15B110 (MB 228.3)
MAN M3275-1
VOLVO VDS-3
REANULT RLD-2
MACK EO-N
CATERPILLAR CAT ECF-1a
MTU Type-2
CUMMINS CES 20078
DETROIT DIESEL DDC 93K215
DEUTZ DQC III-18
ISUZU

The API CI-4 standard provides the protection and durability of engines equipped with EGR:

- Dispersant and antioxidant properties: protection against increased viscosity due to residues and clogging of the oil filter.
- Very high anti-wear ability: protection against liner polishing.
- High detergent ability: it protects the pistons and reduces deposits on them.

The cold viscosity grade significantly improves protection against wear at start-ups and saves fuel on frequent starts.

Anti-corrosion, anti-rust, anti-foam.

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.





PERFORMANCE LUBRICATION

PRODUCT INFORMATION

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

SAE VISCOSITY:	15W-40	FREEZING POINT:	-30°C / -22 F
VISCOSITY AT 100°C:	15 mm ² /s	FLASHPOINT:	230°C / 446 F
VISCOSITY AT 40°C:	125 mm ² /s	SULPHATED ASH:	1.32 % Mass
VISCOSITY INDEX:	123	TBN:	10.3 mg KOH/g

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

