



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL FLEET CORE 20W-50

Multigrade lubricant for heavy diesel engines

DESCRIPTION

Multigrade lubricant for diesel engines, turbocharged and non-turbocharged, long life, in heavy duty vehicles: trucks, buses, public works machinery, etc.

BENEFITS

STANDARDS: ACEA E7
API CI-4 / SL

SPECIFICATIONS: JASO DH-1
GLOBAL DHD-1
DTFR 15B110 (MB 228.3)
DEUTZ DQC II-18

API CI-4 provides protection and durability for engines equipped with EGR:

- Dispersant and antioxidant properties: protection against viscosity increase in the presence of residues and filter clogging.
- Very high anti-wear power: protection against liner polishing.
- High detergent power: protects pistons and reduces piston deposits.

The cold viscosity grade significantly improves wear protection at start-up and saves fuel during frequent starts.

Anti-corrosion, anti-rust, anti-foam.

CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.





PERFORMANCE LUBRICATION

PRODUCT INFORMATION

TECHNICAL CHARACTERISTICS

VISCOSECITY SAE:	20W-50	FREEZING POINT:	-21 °C / -5.8 °F
VISCOSECITY AT 100°C:	18 mm ² /s	FLASH POINT:	230 °C / 446 °F
VISCOSECITY AT 40°C:	150 mm ² /s	SULPHATED ASHES:	1,32 % Mass
VISCOSECITY INDEX:	133	TBN:	10,3 mg KOH/g

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

