



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL FLEET ESSENTIAL 10W

Mono-grade lubricant for heavy diesel engines

DESCRIPTION

Mono-grade lubricant for heavy diesel engines, as well as for hydraulics in civil engineering machinery.

BENEFITS

STANDARDS:

ACEA E2
API CF-4 / SG

SPECIFICATIONS:

MB 228.0
MAN 270
MIL-L-2104 E
CAT TO-2
ALLISON C-4
ZF TE-ML 03 B

Also suitable for hydraulic circuits and torque converter transmissions.

- Protects the engine.
- Resistance to rust and corrosion.
- Keeps mechanical parts clean.

CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

TECHNICAL CHARACTERISTICS

VISCOSITY SAE:	10W	FREEZING POINT:	-27 °C / -16.6 °F
DENSITY AT 15°C:	0,870	FLASH POINT:	226 °C / 438.8 °F
VISCOSITY AT 100°C:	5.8 mm ² /s	SULPHATED ASHES:	1 % Mass
VISCOSITY AT 40°C:	35 mm ² /s	TBN:	5 mg KOH/g
VISCOSITY INDEX:	95		

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

