



PERFORMANCE LUBRICATION

## PRODUCT INFORMATION

# GLOBAL FLEET ESSENTIAL 25W-60

*Lubricant for diesel engines*

## DESCRIPTION

A mineral based multigrade lubricant for turbocharged or naturally aspirated diesel engines operating under severe conditions.

## BENEFITS

**STANDARDS:** API CF-4  
DF-4

Recommended for heavily loaded diesel engines and passenger transport where the use of an API CF-4 or DF-4 standard oil is recommended.

Offers high protection thanks to its high viscosity with adhesion capacity, helping to control oil pressure and power. Excellent ability to reduce oil consumption and prevent leakage.

## CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

## TECHNICAL CHARACTERISTICS

<b>VISCOSITY SAE:</b>	25W-60	<b>FREEZING POINT:</b>	-24 °C / -11.2 °F
<b>DENSITY AT 15°C:</b>	0.890 g/cm <sup>3</sup>	<b>FLASH POINT:</b>	265 °C / 509 °F
<b>VISCOSITY AT 100°C:</b>	24 mm <sup>2</sup> /s	<b>SULPHATED ASHES:</b>	1,05 % Mass
<b>VISCOSITY AT 40°C:</b>	240 mm <sup>2</sup> /s	<b>TBN:</b>	7,12 mg KOH/g
<b>VISCOSITY INDEX:</b>	125		

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

