



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL FLEET ESSENTIAL SAE 30

Mono-grade lubricant for heavy diesel engines

DESCRIPTION

Single grade lubricant for turbo compressed or naturally aspirated diesel engines. With high detergent and dispersing power. Indispensable for engines operating under severe load and temperature conditions (transport, construction machinery, agriculture, marine engines and static engines).

BENEFITS

STANDARDS: ACEA E2
API CF-4 / SG

SPECIFICATIONS: MB 228.0
MAN 270
MTU Type 1
MIL-L-2104 E
CAT TO-2
ALLISON C-4
ZF TE-ML 02C

Also suitable for hydraulic circuits and torque converter transmissions.

- Very low ash content.
- High thermal stability.
- Excellent detergency and dispersancy to ensure perfect engine cleanliness
- Avoid polishing of shirts.
- Reduces engine ring wear and ashing, resulting in higher engine performance and longer lubricant life.

CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.





PERFORMANCE LUBRICATION

PRODUCT INFORMATION

TECHNICAL CHARACTERISTICS

<i>VISCOSITY SAE:</i>	30	<i>FREEZING POINT:</i>	-27 °C / -16.6 °F
<i>DENSITY AT 15°C:</i>	0,870	<i>FLASH POINT:</i>	226 °C / 438.8 °F
<i>VISCOSITY AT 100°C:</i>	12 mm ² /s	<i>SULPHATED ASHES:</i>	0,67 % Mass
<i>VISCOSITY AT 40°C:</i>	100 mm ² /s	<i>TBN:</i>	4,7 mg KOH/g
<i>VISCOSITY INDEX:</i>	110		

Rev. 04/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

