



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

## ***GLOBAL FLEET ESSENTIAL 15W-40***

***Multigrade lubricant for heavy diesel engines***

### **DESCRIPTION**

Multigrade lubricant for diesel engines under high operating conditions. Heavy transport, public works, agricultural machinery, mixed fleets, marine diesel engines. Compatible with Euro I, Euro II and Euro III engines.

### **BENEFITS**

**STANDARDS:** ACEA E2 / E3-96 Issue 4  
API CG-4 / SL

**SPECIFICATIONS:** MB 228.1  
MAN 271  
VOLVO VDS  
CUMMINS CES 20071/72  
DEUTZ DQC I-02  
MACK EO-L  
MTU Type 2  
MIL-L-2104 E  
MIL-L-46152E

- High thermal stability, can be used at high temperatures.
- Facilitates engine start-up and provides better hot and cold lubrication.
- Prevents the formation of residues, varnish deposits and sludge. Very low ash content.
- Avoid polishing of shirts.
- Excellent anti-wear performance ensures superior engine longevity.
- Very high anti-rust, anti-corrosion, anti-rust and anti-foam properties.
- High detergent and dispersing power.

Rev.04 /25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.





PERFORMANCE LUBRICATION

## PRODUCT INFORMATION

### CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

### TECHNICAL CHARACTERISTICS

<b>VIScosity SAE:</b>	15W-40	<b>FREEZING POINT:</b>	-27 °C / -16.6 °F
<b>VIScosity AT 100°C:</b>	14.4 mm <sup>2</sup> /s	<b>FLASH POINT:</b>	225 °C / 437 °F
<b>VIScosity AT 40°C:</b>	115 mm <sup>2</sup> /s	<b>SULPHATED ASHES:</b>	1,10 % Mass
<b>VIScosity INDEX:</b>	127		

Rev.04 /25



[globalracingoil.com](http://globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

