



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

SCOOTER EXTREM 5W40

100% synthetic lubricant for scooter

DESCRIPTION

A 100% synthetic-based lubricant specially designed for old and modern Scooters and Maxi Scooters, equipped with 4-stroke engines, all engine sizes, with or without post-catalytic systems.

All scooters used in urban and intercity travel.

PERFORMANCE

STANDARDS: API SN
JASO MA

Formulated with special additives that give it high chemical stability and resistance to oxidation. With a high detergent ability, it keeps the engine clean and free of carbon deposits. Its high fluidity allows quick starts even at low temperatures.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use. Not suitable for engines with a wet clutch.

TECHNICAL FEATURES

SAE VISCOSITY:	5W-40	FREEZING POINT:	-36 °C / -32.8 °F
VISCOSITY AT 100°C:	14.5 mm ² /s	FLASHPOINT:	225 °C / 437 °F
VISCOSITY AT 40°C:	91.75 mm ² /s		
VISCOSITY INDEX:	165		

Rev. 07/25



globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

